

GLASS DOOR MERCHANDISERS

ICE MERCHANDISERS

MODEL	SWING DOORS	CU. FT.	FLOOR RACKS	HP	AMPS	CRATED WEIGHT	CABINET DIMENSIONS		
							L	D†	H
WITH TANK									
GDIM-26	1	26	1	1/3	9.8	325	30	29 1/2	78 1/4
GDIM-49	2	49	2	1/2	10.2	505	54	29 1/2	78 1/4
WITHOUT TANK									
GDIM-26NT	1	26	1	1/3	9.8	375	30	29 1/2	78 1/4
GDIM-49NT	2	49	2	1/2	10.2	500	54	29 1/2	78 1/4

Rosewood and black vinyl exterior available at no extra charge.
 † Depth does not include 13/8" for door handle.



GDIM-26

Our floor space saving ice merchandisers uniformly match True GDM refrigerators and freezers.



GDIM-26NT



GDIM-49

FEATURES/BENEFITS

- Oversized, environmentally friendly (134A) refrigeration system, factory sealed and pre-lubricated for long life.
- Holds 20°F to 25°F.
- Exterior - durable and permanent non-peel or chip white laminated vinyl.
- Interior - attractive, NSF approved, white aluminum with 300 series stainless steel floor.
- GDIM-26 & GDIM-49 standard with 12" basin to protect from melt-down of product.
- GDIM-26NT & GDIM-49NT standard without 12" basin for additional capacity requirements (no extra charge).
- Standard backguard and floor rack improve airflow.
- Capacity - GDIM-26 holds 50 eight pound bags; GDIM-49 holds 100 eight pound bags. GDIM-26NT holds 54 eight pound bags; GDIM-49NT holds 117 eight pound bags.
- Fluorescent interior lighting.
- Integrated door light (IDL) standard.
- Energy efficient, triple pane, thermal insulated glass doors.
- Foamed-in-place polyurethane high density cell insulation (CFC Free).
- Automatic defrost system time-initiated, temperature-terminated.
- Automatic evaporator fan motor delay during defrost cycle.
- Minimum wattage heater in cabinet frame and doors.
- Bottom mount compressor.
- Energy efficient.
- Available with optional legs or 2 1/2" diameter castors.
- Optional black interiors available. Upcharge and lead times will apply.
- See our website www.truemfg.com for the latest color & sign offerings.
- **Bottom Mounted Units Have...**
- Allows for top storage.
- Compressor can be serviced easily, and accessed by a single repairman.

Remote cabinets available 14% off list (condensing units supplied by others; system comes standard with 404A expansion valve and requires R404A refrigerant). Consult factory technical service dept. for BTU information.